

DECLARATION OF PERFORMANCE

Declaration of performance according to Regulation (EU) 305/2011

n. 091CPR13.07

- Unique identification code of the product type:
041-00-001A, residential space heating appliance fired by wood pellets
EN 14785:2006
- Type, batch or serial number or any other element allowing identification of the construction product as required under Art. 11(4):
INFINITY
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Residential space heating appliance fired by wood pellets
- Name, registered trade name or registered trademark and contact address of the manufacturer as required by Art. 11 (5):
Ravelli S.p.A.
Via A. Kupfer, 31
25036 Palazzolo s/O (Bs) Italia
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The notified laboratory TÜV Rheinland Energie GmbH (NB 2456) performed the determination of the product type on the basis of type testing under system 3 and issued test report K19022016T1
- Declared performance

Harmonized technical specification:	EN 14785:2006
Essential characteristics	Performance
Firesafety	
Reaction to fire	AI
Distance to combustible materials	Minimum distances (mm): rear = 100 sides = 150 front = 800 ceiling = 600 floor = —
Risk of burning fuel falling out	Pass
Emission of combustion products (at 13% of O ₂)	Nominal heat output CO 0,002 % NO _x 160,3 mg/Nm ³ OGC 1,08 mg/Nm ³ PM 16,11 mg/Nm ³ Reduced heat output CO 0,025 % OGC 7,15 mg/Nm ³
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum operating pressure	-
Flue gas temperature at nominal heat output	177 °C
Mechanical resistance (to carry a chimney/flue)	NPD
Nominal heat output	9,2 kW
Room heating output	9,2 kW
Water heating output	-
Efficiency	η 89,4 % Nominal heat output η 94,2 % Reduced heat output

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer

Giovanni Scarlini, CEO

(name and title)

Place

Palazzolo s/O

Date

12/09/2016

Sign

